Simultaneous Speech Extraction for Multiple Target Speakers under the Meeting Scenarios

Bang Zeng^{1,2}, Hongbing Suo³, Yulong Wan³, and Ming Li^{1,2*}

 School of Computer Science, Wuhan University, Wuhan, China
 Suzhou Municipal Key Laboratory of Multimodal Intelligent Systems, Duke Kunshan University, Kunshan, China
 Data & AI Engineering System, OPPO, Beijing, China

Abstract. The common target speech separation directly estimate the target source, ignoring the interrelationship between different speakers at each frame. We propose a multiple-target speech separation model (MTSS) to simultaneously extract each speaker's voice from the mixed speech rather than just optimally estimating the target source. Moreover, we propose a speaker diarization (SD) aware MTSS system (SD-MTSS), which consists of a SD module and MTSS module. By exploiting the TSVAD decision and the estimated mask, our SD-MTSS model can extract the speech signal of each speaker concurrently in a conversational recording without additional enrollment audio in advance. Experimental results show that our MTSS model achieves 1.38dB SDR, 1.34dB SI-SDR, and 0.13 PESQ improvements over the baseline on the WSJ0-2mix-extr dataset, respectively. The SD-MTSS system makes 19.2% relative speaker dependent character error rate (CER) reduction on the Alimeeting dataset.

Keywords: Target speech separation, Interrelationship, Speaker Diarization, Target Speaker Voice Activity Detection, SD-MTSS.

1 Introduction

In the real world, noise and speaker interference can degrade the system performance of back-end speech applications. Speech separation effectively solves this problem by extracting the target speech from the mixed utterance. Early methods called blind speech separation, such as Deep Clustering (DPCL) [1], Deep Attractor Network (DANet) [2], and Permutation Invariant Training (PIT) [3, 4], can separate each source from a mixed speech. These algorithms formulated in the time-frequency domain have an upper bound on reconstructing waves [5]. Recent solutions in the time-domain, such as Time-Domain Audio Source Separation (Tas-Net) [5,6] and Dual-Path RNN (DPRNN) [7], break through the constraints and achieve state-of-the-art performance in the separation task. Despite this, the unknown number of speakers and the global permutation problem are still two challenges for blind speech separation.

^{* †} Corresponding Author, E-mail: ming.li369@dukekunshan.edu.cn

To address the above two problems, a framework called speaker extraction [8, 9] or target speech separation [10–12] can extract a target speaker' speech from the mixed audio by utilizing an auxiliary reference speech of the target speaker. However, it is required to filter out multiple target speakers in certain tasks, e.g., meeting scenarios. The common approach is to infer the mixed speech for several times and each process is independent of the other, ignoring the interrelationship between the speech of different speakers at each frame. In addition, obtaining the reference speech of multiple target speakers in advance is difficult to achieve. Considering the aforementioned problems, repeatedly processing the mixture speech towards different target speakers separately may not be a feasible solution.

It is worth noting that speech in the meeting scenario usually has a long duration and contains both single-talker and overlapped voice segments. Thus, it is possible to use the single-talker segments as the reference speech for participants instead of obtaining additional speech for enrollment. Speaker Diarization (SD) [13] technology is very suitable for this role. SD aims to slice different speaker segments in a continuous multiple speakers conversation and determine which speaker each segment belongs to. More recently, MC-TS-VAD [14], which selects TSVAD as the post-processing module and employs cross-channel self-attention, achieved the best result in the Multi-party Meeting Transcription Challenge (M2Met) [15].

In this work, we propose the MTSS model, which is a speech extraction method for multiple target speakers. The MTSS model infers each speaker's mask simultaneously and limits their estimated masks to be sum to 1. We consider that the energies of different speakers at each frame are not independent to each other. Moreover, we propose the SD-MTSS framework, which associates target speech separation with speaker diarization. We select the TSVAD system as the speech diarization network. Based on the decisions from TSVAD [16], we can obtain each speaker's reference speech directly from the mixed audio. Then, each speaker's reference speech is fed into the MTSS module in the separation stage.

The rest of this work is organized as follows. In Section 2, we present the architecture of the proposed MTSS and SD-MTSS models. In Section 3, we report the experimental setup. In Section 4, we report the results and discussions. The conclusions are drawn in Section 5.

2 Methods

2.1 Multiple target speech separation model

Backbone The backbone of the Multiple Target Speech Separation (MTSS) model is SpEx+ [17], which consists of two twin speech encoders, a speaker encoder, a speaker extractor, and a speech decoder. The twin speech encoder model the input sequence and auxiliary speech in a common latent space through sharing the structure and parameters. The speaker encoder model is a ResNet-based speaker classifier used to generate the speaker embedding of the reference




Fig. 1. The details of the MTSS model. aux_{s_1} and aux_{s_2} are the reference wave of two speakers. m is the mixed wave. "C" denotes the operation of concatenate. \otimes is an operation for element-wise product.

speech. The speaker extractor takes both the speaker embedding and the output of the twin speech encoder as the inputs, and then produces masks in three different scales. The speech decoder outputs the estimation by multiplying the input sequence and the multi scales masks.

MTSS model Here, we propose a speech extraction model for multiple target speakers (MTSS), which can simultaneously separate the speech of each speaker present in the conversation. The schematic diagram of the MTSS model is shown




Fig. 2. Schematic of the SD-MTSS system. γ is a threshold (0.5 often). m is the mixed input. s_1 , s_2 represent the two speakers presented in the mixture. aux_{s_1} , aux_{s_2} denote the reference speech of two speakers. est_{s_1} , est_{s_2} denote the estimations of two speakers. d_{s_1} , d_{s_2} indicates the binarized TSVAD decision.

in Figure 1. Unlike the original SpEx+ neural network takes only one speaker's reference speech, MTSS takes both two speaker's reference speech as the inputs and process them separatly. Moreover, we replace the ReLU with softmax to establish the relationship between the masks of each speaker in the same utterance. We believe that taking the interrelation into account will improve the final separation performance of the model. Because in the definition of binary masks, each time-frequency cell belongs to a speaker with stronger energy. Specifically, the responses of MTSS s'_1 , s'_2 can be formulated as:

$$(s'_1, s'_2) = m \otimes \{ \operatorname{softmax}(cat(mask_{s_1}, mask_{s_2})) \}$$
 (1)

where $mask_{s_1}$, $mask_{s_2} \in \mathbb{R}^{N \times 1 \times T}$. \otimes is an operation of element-wise product. softmax(*) and cat(*) indicates that a softmax function and concatenation operates on the penultimate dimension, respectively. N is the feature dimension and T is the time length. We also implement a multi-task learning framework for the target speech separation.

2.2 SD-MTSS system

Considering that it is feaible to apply speaker diarazation techniques to target speech separation, we expend the MTSS to speaker diarization (SD) aware MTSS (SD-MTSS) system. The SD-MTSS system architecture is shown in Figure 2. Rather than requiring additional registration, SD-MTSS directly obtains reference speech from the long utterance itself through the SD module. In real applications, the single-channel SD approach [18] can be used here. The SD-MTSS system consists of a SD module and a MTSS module. The SD module produces the TSVAD decision for multiple speakers, which are the probabilities of each speaker's presence at the frame level. The MTSS module adopts each

speaker's reference speech from the SD module and the mixture audio as inputs, and then outputs the estimation for multiple target speakers.

Using the TSVAD decision, we can get the single-talker audio segments as the reference speech for each speaker. The scheme of obtaining single-talker segments in Figure 2 is organized as follows. We use $m \in \mathbb{R}^{1 \times T}$ indicate the input sequence. s_1 and s_2 indicate the two different speakers in the mixture. First, the TSVAD decision is passed through a threshold mechanism and produces the binarized results d_{s_1} and d_{s_2} . Its values consist of 0 and 1. Then the reference speech can be formulated as:

$$aux_{s_1} = m \otimes \tilde{d_{s_1}} \tag{2}$$

$$\tilde{d_{s_1}} = (d_{s_1} - d_{s_1} \otimes d_{s_2})$$
 (3)

$$aux_{s_2} = m \otimes \tilde{d_{s_2}} \tag{4}$$

$$\tilde{d_{s_2}} = (d_{s_2} - d_{s_1} \otimes d_{s_2})$$
 (5)

where $\tilde{d_{s_1}}$ and $\tilde{d_{s_2}}$ indicates the mono-speaker activity part of d_{s_1} and d_{s_2} , respectively. $d_{s_1}, d_{s_2} \in \mathbb{R}^{1 \times T}$, \otimes indicates the element-wise product. \otimes is an operation of element-wise product. Selected continuous audio segments of aux_{s_1} and aux_{s_2} will be fed into the MTSS module as the reference speech for the subsequent separation task.

2.3 Speaker diarization (SD) module

The SD module in this work consists of a clustering-based module for target speaker embedding extraction and a TSVAD system for diarization results refinement [14].

Clustering-based module The affinity matrix extraction model of TSVAD is based on the neural network in [19], using an LSTM-based model in similarity measurement for speaker diarization. It consists of two bidirectional long short-term memory networks (Bi-LSTM) layers and two fully connected layers. The LSTM-based model first splits the entire audio into short speech clips and extracts the speaker embedding of all segments. Then it takes these segments as inputs and produces the initialized diarization result through adopting spectral clustering.

TSVAD system The architecture of the TSVAD [14] system is shown in Figure 3, which consists of three parts:

1. A pre-trained speaker embedding model ResNet [20] based on ArcFace [21] and cosine similarity scoring. The dimension of the speaker embedding layer is 128 and the margin and softmax prescaling of the ArcFace is 0.2 and 32.




Fig. 3. The structure of the TSVAD system. The Front-end share the same architecture with the pre-trained speaker embedding model. The target speaker embedding concatenates with the frame-level speaker embedding repeatedly and then is fed into the Back-end.

- 2. A front-end model with the same architecture as the pre-trained model is used to extract the frame-level speaker embedding.
- 3. A back-end model consists of an encoder layer, a BiLSTM layer, a liner layer, and a sigmoid function.

First, the pre-trained speaker embedding model extracts the target speaker embeddings. Meanwhile, the front-end network loads its parameters to extract the frame-level speaker embeddings. The target speaker embeddings are repeatedly concatenated with the frame-level speaker embeddings and then fed into the back-end. Next, the encoder layer of the back-end model produces each target speaker's detection state. The BiLSTM layer inputs these detection states and models the relationship between speakers. Finally, the linear layer coupled with a sigmoid function generates each speaker's final decision (TSVAD decision). More details can be found in [14].

3 Experiment Setup

3.1 Dataset

Datasets for MTSS model: We simulated a commonly used two-speakers mixture datasets WSJ0-2mix-extr¹ (20000 utterances in training set, 5000 utterances in validation set, and 3000 utterances in test set, respectively), the sampling rate of which is 8KHz. The simulation process is the same as [17], and the only difference is that we produce a couple of target speakers speech (s_1, s_2) and reference speech (aux_{s_1}, aux_{s_2}) for each mixture utterance, while [17] only select the first talker as the target speaker. The utterance from s_1 and s_2 are set in a relative SNR between 0 to 5 dB. The average SI-SDR of mixed speech is 2.50dB and -2.50dB when it takes s_1 and s_2 as the reference.

Datasets for SD-MTSS model: For the SD module, we use the training set of Alimeeting [15] to train the clustering-based affinity matrix extraction neural network. Alimeeting contains 118.75 hours of speech data, including 104.75 hours (426 speakers) of the training set, 4 hours (25 speakers) of the validation set, and 10 hours of the test set. For the TSVAD model in the SD module, we create a simulated datesets based on the Alimeeting training set. The simulation scheme is the same as [14]. For MTSS module, we use the Libri-2mix [26] as the training set, which has a sampling rate of 16KHz. We select the signal channel signal on channel 0 of the two-speakers samples from the Eval-Ali-far and Test-Ali-far subsets of Alimeeting to evaluate the performance of SD-MTSS model.

3.2 Implementation details

To compare with the baseline, the hyperparameters and learning schedule of MTSS module are set the same as [17]. The number of filters in the encoder is 256, the number of convolutional blocks in each repeat is 8, the number of repeat is 4, the number of channels in the convolutional blocks is 512, the kernel size of the convolutional blocks is 3. The hyperparameters of the network are shown in Table 1.

Symbol	Settings	Description
L1, L2, L3	20, 80, 160	Lengths of the Encoder filter
N	256	Number of filters in Encoder
X	8	Number of convolutional blocks
В	256	Number of channels in bottleneck conv blocks
H	512	Number of channels in convolutional blocks
P	3	Kernel size in convolutional blocks
spk_emb_dim	256	Dimension of the speaker embedding

Table 1. Hyperparameters of the MTSS module.

¹ https://github.com/xuchenglin28/speaker_extraction

The initial learning rate is $1e^{-3}$ and decays by 0.5 if the accuracy of validation set is not improved in 2 epochs. Early stopping is applied if the accuracy of validation set have not improved for 6 epochs. As the same in SpEx+ [17], We use the multi-task learning implementation for training with two objectives. We use the scale-invariant signal-to-distortion ratio [32] (SISDR) as the loss output speech quality and a cross-entropy (CE) loss for speaker classification:

$$SISDR = 10 \log_{10} \left(\frac{||e_{target}||^2}{||e_{res}||^2} \right)$$

$$= 10 \log_{10} \left(\frac{||\frac{\hat{s}^T s}{||s||^2} s||^2}{||\frac{\hat{s}^T s}{||s||^2} s - \hat{s}||^2} \right)$$
(6)

$$\hat{s} = e_{target} + e_{res} \tag{7}$$

$$\mathcal{L}_{SI-SDR} = -\left[(1 - \alpha - \beta)SISDR_{l_1} + \alpha SISDR_{l_2} + \beta SISDR_{l_3} \right]$$
 (8)

$$\mathcal{L}_{CE} = -\sum_{i=1}^{N_s} I_i \log \left(\sigma(W \cdot v)_i \right)$$
 (9)

where \hat{s} represent the estimated speech. l_1 , l_2 and l_3 represent three different multi-scale estimation, respectively. α and β are the weights to different scales. e_{target} and e_{res} indicate the estimated speech's orthogonal projection and residual w.r.t. the reference speech, respectively. N_s is the number of speakers in the training datasets. W represents a weight matrix, $\sigma(\cdot)$ represents a softmax function. The multi-task objective function for single speaker is defined as:

$$\mathcal{L}_{\text{multi}} = \mathcal{L}_{\text{SI-SDR}} + \mathcal{L}_{\text{CE}} \tag{10}$$

The overall objective function for our MTSS model is defined as:

$$\mathcal{L}(\theta|m, aux_{s_{1,2}}, spk_{1,2}, I_{s_{1,2}}) = \lambda_1 \mathcal{L}_{\text{multi}_{\text{spk1}}} + \lambda_2 \mathcal{L}_{\text{multi}_{\text{spk2}}}$$
(11)

where m is the input sequence, $aux_{s_{1,2}}$ are the reference speeches of two speakers, spk_1 and spk_2 are the target speeches of two speakers, λ_1 and λ_2 are the weights of scale-invariant signal-to-distortion ratio (SI-SDR) loss and crossentropy (CE) loss, respectively. In this work, we set $\lambda_1 = 0.5$ and $\lambda_2 = 0.25$ as the default values.

The SD module chooses the Adam and binary cross-entropy loss as the optimizer. The input chunk size is 16s, and the acoustic feature is 80-dim log Mel-filterbank energies with a frame length of 25ms and a frame shift of 10ms. The training details can be found in [27]. The training steps of the SD modeules are as follow:

- 1. Transfer the pre-trained speaker embedding model's parameters to the frontend model in the TSVAD model. Maintain the front-end model in a fixed state while focusing our training efforts on the back-end model.
- 2. Subsequently, once the back-end model reaches convergence, we proceed to unfreeze the front-end model and embark on a joint training phase for the entire model, spanning an additional 10 epochs.
- 3. In the final stage, we initiate fine-tuning of the model using the AliMeeting training set, extending this process over 200 epochs while employing a learning rate of $1e^{-5}$.

The Diarization Error Rate (DER) of the single-channel SD module [18] on the test set of Alimeeting are shown in the Table 2. We use the offline model as the SD system in our proposed SD-MTSS model. The SD module has a 4.12% DER on the evalution set of the Alimeeting dataset.

Table 2. The DERs(%) of the single-channel offline and online SD systems on AliMeeting Eval set.

model	2-spk	3-spk	4-spk	Total
offline	0.89	6.63	5.47	4.12
online	1.90	8.36	12.12	8.14

We evaluate our proposed models for two steps: 1) Examining the performance of MTSS on WSJ0-2mix-extr dataset. We train the MTSS model with a pre-trained model on the training set of WSJ0-2mix-extr. Then, we compare MTSS-Softmax and MTSS-ReLU in terms of SDRi, SI-SDR, and PESQ. 2) Examining the performance of SD-MTSS system on Alimeeting. We compare SpEx+² (implemented by ourself with using Libri-2mix dataset as training set) and SD-MTSS model in terms of spekaer dependent character error rate (CER)[28].

4 Results and Discussions

4.1 Results on WSJ0-2mix-extr

The results of our proposed MTSS model and the baseline system is shown in Table 3. Since we used the same simulation test set as [17] uses, we directly use the evaluation results of SpeakerBeam, SBF-MTSAL-Concat, TseNet, SpEx, and SpEx+ in [17]. As shown in Table 3, SpEx+ [17] is the baseline which we implemented, and MTSS are the model we proposed. Our proposed MTSS model achieves significantly better results across all the metrics. The samples of separated audio are available at this link ³. Specifically, MTSS-Softmax outperforms

² https://github.com/gemengtju/SpEx_Plus

³ https://github.com/ZBang/SD-MTSS

Table 3. SDR(dB), SI-SDR(dB), and PESQ of separated speech using the MTSS method on the WSJ0-2mix-extr dataset. **N** indicates the number of outputs per inference. s_1 and s_2 indicate the different speaker of the mixture. **MTSS-ReLU**: Using ReLU as the activation function and do not impose constraints on masks. **MTSS-Softmax**: Using softmax function to limit the sum of masks to 1.

Methods		SDR		SI-SDR		PESQ	
		s1	s2	s1	s2	s1	s2
Mixture		2.60	-2.14	2.50	-2.50	2.31	1.86
SpeakerBeam [22]	1	9.62	-	9.22	-	2.64	-
SBF-MTSAL-Concat [23] TseNet [24] SpEx [25] SpEx+ [17]		11.39	-	10.60	-	2.77	-
		15.24	-	14.73	-	3.14	-
		17.15	-	16.68	-	3.36	-
		18.54	-	18.20	-	3.49	-
Pre-trained model ²	1	18.15	16.42	17.55	15.89	3.44	3.28
MTSS-ReLU		19.18	17.29	18.72	16.84	3.56	3.39
MTSS-Softmax	2	19.92	17.42	19.54	16.99	3.62	3.41

SpEx+ with relative improvements of 7.4% in terms of SDR, 7.3% in terms of SI-SDR, and 3.2% in terms of PESQ, respectively. In addition, we get better improvement on each speaker (s_1, s_2) while extracting their target speech simultaneously. Comparing the results of MTSS-ReLU and MTSS-Softmax, we can conclude that setting the constraint for each speaker's mask mainly contribute to the improvements, and the interrelationship between different speakers at each frame benefits the model to extract the target source.

Table 4. Average speaker dependent CER(%) results of SD-MTSS on Eval_Ali_far and Test_Ali_far sets. N indicates the number of outputs per inference. Re indicates that the model is implemented by ourself. We use MTSS-Softmax model as the MTSS module of the SD-MTSS system.

Methods		Eval		0
Mixture	-	96.70	95.51	95.83
SpEx+ [17] (Re)	1	45.80	43.79	44.34
SD-MTSS	2	35.97	35.78	35.83

^{*} We use WeNet [30] as the speech recognition model in this experiments. The wenet model is trained by WeNetSpeech [31] and our inhouse data together with approximately 15K hours.

4.2 Results on Alimeeting

The speech recognition results of our proposed SD-MTSS system are shown in Table 4. Here, we report the average speaker independent CER results on the Eval_Ali_far and Test_Ali_far subsets of Alimeeting. It is important to note

that we have adopted Minimum Variance Distortionless Response (MVDR⁴) beamformer on the mixture in advance. Due to multi-speaker interference, many insertion errors are generated in recognition of the mixed speech. The difference between SpEx+ and our proposed SD-MTSS system is that the SD-MTSS can extract the speech of each speaker simultaneously in one inference and does not need an enrollment wave in advance. Compared with the SpEx+ model, the SD-MTSS model achieves a 21.4% and 18.3% relative average speaker dependent CER reduction on Eval Ali far and Test Ali far subsets of the Alimeeting, respectively. Since we only need to evaluate the effectiveness of SD-MTSS model, we did not train the recognition and separation models jointly. As far as we know, joint training and fine-tuning with Alimeeting datasets can improve final recognition performance [29]. The results of our proposed SD-MTSS system are shown in Table 4. Since we evaluate the system on the far-field data and use the corresponding close-talking data as the ground truth, the model does not performance well in terms of SDRi and SI-SDRi. Nevertheless, from Table 4, we can conclude that our proposed multiple target speech separation model surpasses the pre-trained model (SpEx+) with a large margin in terms of SI-SDRi.

5 Conclusions

In this work, we propose a Multiple Target Speech Separation (MTSS) model which can simultaneously extract each speaker's voice from the mixed speech. To establish a relationship between different speakers in each frame, we constrain the sum of each speaker's estimated mask to 1 when extracting their speech simultaneously. Moreover, we proposed a speaker diarization multiple target speech separation system (SD-MTSS), which consists of a speaker diarization (SD) module and a MTSS module. By associating the speaker diarization task and the target speech separation task together, we do not require the additional reference speech for enrollment. The experimental results show that our proposed MTSS model significantly improves the separation performance on WSJ0-2mix-extr datasets. In addition, the SD-MTSS model outperforms the baseline by a large margin in terms of speaker independent CER on the Alimeeting datasets. For future works, we will implement our method with different state-of-art networks and improve the system's performance in the far-field scenarios.

6 Acknowledgements

This research is funded in part by the National Natural Science Foundation of China (62171207), Science and Technology Program of Suzhou City (SYC2022051) and OPPO. Many thanks for the computational resource provided by the Advanced Computing East China Sub-Center.

⁴ https://github.com/funcwj/setk

References

- 1. John R Hershey, Zhuo Chen, Jonathan Le Roux, and Shinji Watanabe, "Deep clustering: Discriminative embeddings for segmentation and separation," in Proc. of ICASSP, 2016.
- Zhuo Chen, Yi Luo, and Nima Mesgarani, "Deep attractor network for single-microphone speaker separation," in Proc. of ICASSP, 2017, pp. 246–250.
- 3. Dong Yu, Morten Kolbæk, Zheng-Hua Tan, and Jesper Jensen, "Permutation invariant training of deep models for speaker-independent multi-talker speech separation," in Proc. of ICASSP, 2017, pp. 241–245.
- Morten Kolbæk, Dong Yu, Zheng-Hua Tan, and Jesper Jensen, "Multitalker speech separation with utterance-level permutation invariant training of deep recurrent neural networks," IEEE transactions on audio, speech, and language processing, vol. 25, no. 10, pp. 1901–1913, 2017.
- 5. Yi Luo and Nima Mesgarani, "Tasnet: time-domain audio separation network for real-time, single-channel speech separation," in Proc. of ICASSP, 2018, pp. 696-700.
- Yi Luo, and Nima Mesgarani, "Conv-tasnet: Surpassing ideal time-frequency magnitude masking for speech separation," IEEE transactions on audio, speech, and language processing, pp. 1256–1266, 2019.
- Yi Luo, Zhuo Chen, and Takuya Yoshioka, "Dual-path rnn: efficient long sequence modeling for time-domain single-channel speech separation," in Proc. of ICASSP, 2020.
- 8. Meng Ge, Chenglin Xu, Longbiao Wang, Eng Siong Chng, Jianwu Dang, and Haizhou Li, "Multi-stage speaker extraction with utterance and frame-level reference signals," in Proc. of ICASSP, 2021, pp. 6109–6113.
- Marc Delcroix, Katerina Zmolikova, Tsubasa Ochiai, Keisuke Kinoshita, and Tomohiro Nakatani, "Speaker activity driven neural speech extraction," in Proc. of ICASSP, 2021.
- 10. Quan Wang, Hannah Muckenhirn, Kevin W. Wilson, Prashant Sridhar, Zelin Wu, John R. Hershey, Rif A. Saurous, Ron J. Weiss, Ye Jia, and Ignacio Lopez Moreno, "Voicefilter: Targeted voice separation by speaker-conditioned spectrogram masking," in Proc. of Interspeech, 2018.
- 11. Tingle Li, Qingjian Lin, Yuanyuan Bao, and Ming Li, "Atss-net: Target speaker separation via attention-based neural network," in Proc. of Interspeech, 2020.
- 12. Chen, J., Rao, W., Wang, Z., Lin, J., Ju, Y., He, S., Wang, Y., Wu, Z. (2023) MC-SpEx: Towards Effective Speaker Extraction with Multi-Scale Interfusion and Conditional Speaker Modulation. Proc. INTERSPEECH 2023, 4034-4038, doi: 10.21437/Interspeech.2023-1130
- 13. Quan Wang, Carlton Downey, Li Wan, Philip Andrew Mansfield, and Ignacio Lopz Moreno, "Speaker diarization with lstm," in Proc. of ICASSP, 2018, pp. 5239–5243.
- 14. Weiqing Wang, Xiaoyi Qin, and Ming Li, "Cross-channel attention-based target speaker voice activity detection: Experimental results for the m2met challenge," in Proc. of ICASSP, 2022, pp. 9171–9175.
- 15. Fan Yu, Shiliang Zhang, Yihui Fu, Lei Xie, Siqi Zheng, Zhihao Du, Weilong Huang, Pengcheng Guo, Zhijie Yan, Bin Ma, Xin Xu, and Hui Bu, "M2met: The icassp 2022 multi-channel multi-party meeting transcription challenge," Proc. of ICASSP, pp. 6167–6171, 2021.
- Shaojin Ding, Quan Wang, Shuo yiin Chang, Li Wan, and Ignacio Lopez-Moreno, "Personal vad: Speaker-conditioned voice activity detection," in Proc. of Odyssey, 2020.

- 17. Meng Ge, Chenglin Xu, Longbiao Wang, Eng Siong Chng, Jianwu Dang, and Haizhou Li, "Spex+: A complete time domain speaker extraction network," Proc. of Interspeech, 2020.
- 18. Weiqing Wang, Qingjian Lin, and Ming Li, "Online target speaker voice activity detection for speaker diarization," in Proc. of Interspeech, 2022.
- 19. Qingjian Lin, Ruiqing Yin, Ming Li, Herve Bredin, and Claude Barras, "Lstm based similarity measurement with spectral clustering for speaker diarization," in Proc. of Interspeech, 2019.
- 20. Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun, "Deep residual learning for image recognition," in Proc. of CVPR, 2016, pp. 770–778.
- Jiankang Deng, Jia Guo, Niannan Xue, and Stefanos Zafeiriou, "Arcface: Additive angular margin loss for deep face recognition," in Proc. of CVPR, 2019, pp. 4690–4699.
- Marc Delcroix, Katerina Zmolikova, Keisuke Kinoshita, Atsunori Ogawa, and Tomohiro Nakatani, "Single channel target speaker extraction and recognition with speaker beam," in Proc. of ICASSP, 2018, pp. 5554–5558
- Chenglin Xu, Wei Rao, Eng Siong Chng, and Haizhou Li, "Optimization of speaker extraction neural network with magnitude and temporal spectrum approximation loss," in Proc. of ICASSP, 2019, pp. 6990–6994.
- Xu, Chenglin and Rao, Wei and Chng, Eng Siong and Li, Haizhou, "Time-domain speaker extraction network," in Proc. of ASRU Workshop, 2019.
- 25. Chenglin Xu, Wei Rao, Eng Siong Chng, and Haizhou Li, "Spex: Multi-scale time domain speaker extraction network," IEEE transactions on audio, speech, and language processing, vol. 28, pp. 1370–1384, 2020.
- 26. Joris Cosentino, Manuel Pariente, Samuele Cornell, Antoine Deleforge, and Emmanuel Vincent, "Librimix: An open-source dataset for generalizable speech separation," 2020.
- 27. Weiqing Wang, Danwei Cai, Qingjian Lin, Lin Yang, Junjie Wang, Jin Wang, and Ming Li, "The dku-dukeece-lenovo system for the diarization task of the 2021 voxceleb speaker recognition challenge," arXiv preprint arXiv:2109.02002, 2021.
- 28. Yihui Fu, Luyao Cheng, Shubo Lv, Yukai Jv, Yuxiang Kong, Zhuo Chen, Yanxin Hu, Lei Xie, Jian Wu, Hui Bu, et al., "Aishell-4: An open source dataset for speech enhancement, separation, recognition and speaker diarization in conference scenario," Proc. of Interspeech, 2021.
- Fan Yu, Zhihao Du, Shiliang Zhang, Yuxiao Lin, and Lei Xie, "A comparative study on speaker-attributed automatic speech recognition in multi-party meetings," Proc. of Interspeech, 2022.
- 30. Zhuoyuan Yao, Di Wu, Xiong Wang, Binbin Zhang, Fan Yu, Chao Yang, Zhendong Peng, Xiaoyu Chen, Lei Xie, and Xin Lei, "Wenet: Production oriented streaming and non-streaming end-to-end speech recognition toolkit," in Proc. of Interspeech, Brno, Czech Republic, 2021.
- 31. Binbin Zhang, Hang Lv, Pengcheng Guo, Qijie Shao, Chao Yang, Lei Xie, Xin Xu, Hui Bu, Xiaoyu Chen, Chenchen Zeng, Di Wu, and Zhendong Peng, "Wenet-speech: A 10000+ hours multi-domain mandarin corpus for speech recognition," in Proc. of ICASSP, 2022, pp. 6182–6186.
- 32. J. L. Roux, S. Wisdom, H. Erdogan and J. R. Hershey, "SDR Half-baked or Well Done?," in Proc. of ICASSP, 2022, pp. 626-630, doi: 10.1109/ICASSP.2019.8683855.